

For Today's Firefighters, Today's Technology Voice Pager

*Loaded with the features you want,
Priced for your department's budget*



TRIBUTE911™
THE FIREFIGHTER'S CHOICE

Stay linked to all your department's emergency notifications,
while also monitoring neighboring agencies

PAGER FEATURES: *All features are standard, just choose your frequency.*

- Scan up to eight (8) channels with or without Priority
- Priority channel selectable by user
- Can be programmed as priority scanner only (up to eight (8) channels)
- Digital voice message storage--three (3) minute capacity
- Vibrate, Tone or Voice Alert with message waiting indication
- Up to six (6) 2-tone codes
- Multiple/mixed 2-tone formats programmable for each of the 6 codes
- Up to ten (10) distinctive alert tones available
- Programmable fixed alert
- Programmable tone alert OR voice alert for each code
- Field programmable frequencies and codes
- 12.5 or 25KHz bandwidth programmable by channel
- Programmable/customize voice message for each mode of operation
- Simple single page programming menu
- Four (4) switch selectable modes:
 - Closed** with tone or voice alert
 - Closed** with vibrate alert
 - Open** channel with tone or voice alert
 - Scan** with or without priority
- Pocket size and lightweight
- Drop-in rapid charger standard
- IP54 rating (driving rain)
- Extra loud speaker, 2.5 mm jack for remote ear speaker
- 18 month warranty, extended service plan available
- Can operate with 2 standard AAA batteries (NiMH provided)
- Excellent receiver sensitivity and life per charge specifications
- Protective bullet nylon carrying case with belt clip included

MODELS: **VRP-100 VHF** (149-161 MHz)
 VRP-400 UHF (448-460 and 456-468 MHz)

Operational Bandwidth: +/-4MHz
Number of channels: 8 channels max.
Channel spacing: 12.5 or 25 kHz
Type of Emission: 11KOF3E/16KOF3E
Battery Voltage: 22.4 V DC (NiMH)/3V DC (2xAAA)
Battery Lifetime: 24 hours (nominal)
Operating Temperature: -20° -+50°C (-2° -+122° F)
Size: 2-1/8"W x 3-3/4"H x 1-1/4" D including knobs
and belt clip (or 54 x 95 x 32 mm)
Weight: 3 oz. (or 82 g) without 2 NiMH AAA batteries

RECEIVER

Sensitivity: (12dB SINAD) 0.25 uv (-119dBm)
Squelch Sensitivity: .2 uv (-121 dBm)
Spurious Response: -50dB
Selectivity: -50dB
Frequency stability: +/-2.5ppm
Audio Distortion: Less than 5% at 1kHz
Volume (alert): Over 88dB at 12" (30cm)/erp
Volume (voice): Over 60dB at 12" (30cm)/erp

TRIBUTE 911™ PAGERS are brought to you by:

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

